## Material Safety Data Sheet

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200

Standard must be consulted for specific requirements.

REVO OCE 2007 U.S. Department of Labor

Occupational Safety and Health Administration

461906, 909, 912,915,

(Non-Mandatory Form) Form Approved OMB No. 1218-0072 461918, 921, 924, 927, 930,

461933, 936, 939, 942 IDENTITY (As Used on Label and List) Note: Blank spaces are not permitted. If any item is not applicable, or no Sax True FlowWater Soluble Block Printing Inks information is available, the space must be marked to indicate that. 461945,461948,461951,461954,461957,461960,461978,461906, 461909,461912,461915,461918,461921,461939,461963,461966, 461969, 461972,461975,461981,461924,461927,461930,461933, 461936,461942,443435,443432 Section I Manufacturer's Name Emergency Telephone Number Sax Arts & Crafts 800-558-6696 Address (Number, Street, City, State, and ZIP Code) Telephone Number for Information 2725 S. Moorland Rd. 800-558-6696 New Berlin, WI 53151 Signature of Preparer (optional) Date Prepared: May 11, 2007

# Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s)): **OSHA PEL** ACGIH TLV Other Limits %(optional) Recommended

Product labeling conforms to ASTM D-4236. Approved for the AP seal as per the Art & Craft Materials Institute, Inc. (ACMI). Note: This product has been certified to be non-toxic. This product has been evaluated by a Toxicologist only as per intended usage. DO NOT DEVIATE FROM INTENDED USE.

## Section III - Physical/Chemical Characteristics

Boiling Point	212°F-369°F	Specific Gravity (H <sub>2</sub> O = 1)	1.2-1.7
Vapor Pressure (mm Hg.)	N/A	Melting Point	<32°F
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	Less than 1
Solubility in Water	Dilutable	Appearance and Odor	Thick paste with slight odor

#### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media N/A			
Special Fire Fighting Procedures  Wear self-contained breathing apparatus (pr gear.	essure-demand MSHA/NIOSH approved	or equivalent) and	d full protective
Unusual Fire and Explosion Hazards  Material can spatter above 212°F. Film can be	ourn.		
(Reproduce locally)			

OSHA 174, Sept. 1985

Stability '	Unstable	Stable	Conditions to Avoid Onset of decomposition	is 350°F
Incompatibility (M N/A	aterials to Avoid)	ı		
Hazardous Decomp Oxides of carbo	oosition or Byproon	ducts		
Hazardous Polymerization	May Occur	Will Not Occur	Conditions to Avoid N/A	

#### Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? Irritation with prolonged co	Ingestion? N/A		
Health Hazards (Acute and N/A	Chronic)		debitions force Transport recovered an attraction and approximately appropriate and approximately debit and approximately approx		
Carcinogenicity: N/A	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A		
Signs and Symptoms of Exp N/A	osure				
Medical Conditions Generally Aggravated by Exposure None known					
Emergency and First Aid Procedures  Contact with eyes may cause slight irritation: Flush with water.					

## Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Floor may be slippery; use care to avoid falling. Transfer to containers for recovery or disposal. Keep out of municipal sewers and open bodies of water.

Waste Disposal Method

Incineration at permitted facility. Observe all Federal, State and local laws concerning health and environment.

Precautions to Be taken in Handling and Storing

Keep from freezing-product may coagulate

Other Precautions

N/A

#### **Section VIII - Control Measures**

Respiratory Protection (Specify Type) None required with adequate ventilation & normal usage conditions.				
Ventilation	Local Exhaust N/A	Special N/A		
	Mechanical (General) N/A	Other N/A		
Protective Gloves I	mpervious		Eye Protection Safety Glasses or goggles	
Other Protective Clothing or Equipment N/A				
Work/Hygienic Prac	tices Use protective cream who	ere excessive s	kin contact is likely.	