

319-119/249450

May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard Must Be  
 Consulted for Specific Requirements

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072

Recvd May 2002

IDENTITY (As Used on Label and List)  
 Prang Wax Crayons

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

**SECTION I**

|   |  |
|---|--|
| Manufacturer's Name<br>DIXON TICONDEROGA  | Emergency Telephone Number<br>(419) 625-9545       |
| Address (Number, Street, City, State, and ZIP)<br>1706 HAYES AVENUE<br>SANDUSKY, OHIO 44870 | Telephone Number for Information<br>(419) 625-9545 |
|   | Date Prepared<br>04/25/02                          |
|   | Signature of Preparer (optional)                   |

**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

| Hazardous Components<br>(Specific Chemical Identity; Common Name(s)) | OSHA PEL | ACGIH TLV | Other Limits<br>Recommended %Optional |
|--|----------|-----------|---------------------------------------|
|--|----------|-----------|---------------------------------------|

Products bearing the CP Certified Products or AP Approved Products seals of the Art and Creative Materials Institute, Inc. are certified in a program of Toxicological evaluation by a Medical expert, subject to review by the Institute's Toxicological Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans or cause acute or chronic health problems.

CONFORMS TO ASTM-4236

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

|   |   |
|---|---|
| Boiling Point<br>NA   | Specific Gravity (H2O = 1)<br>NA              |
| Vapor Pressure (mm Hg)<br>NA                                    | Melting Point<br>N/A                          |
| Vapor Density (Air=1)<br>NA                                     | Evaporation Rate<br>(Butyl Acetate = 1)<br>NA |
| Solubility In Water<br>NA                                       |   |
| Appearance and Odor<br>Assorted colors, various sizes, no odor. |   |

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

|   |                         |            |            |
|---|-------------------------|------------|------------|
| Flash Point (Method Used)<br>N/A  | Flammable Limits<br>N/A | LEL<br>N/A | UEL<br>N/A |
| Extinguishing Media<br>Water Spray, Foam, CO2   |                         |            |            |
| Special Fire Fighting Procedures<br>Containers may be subject to ignition by fire and may release toxic or other irritating gases |                         |            |            |

**Unusual Fire and Explosion Hazards**

A self contained breathing apparatus should be used for this exposure.

(Reproduce Locally)

OSHA 174, SEPT. 1985

**SECTION V - REACTIVITY DATA**

|  |                       |                             |
|--|-----------------------|-----------------------------|
| Stability  | Unstable              | Conditions To Avoid<br>NONE |
|  | Stable<br>YES         |                             |
| Incompatibility (Materials To Avoid)   | NONE                  |                             |
| Hazardous Decomposition or Byproducts<br>As with all burning organic matter, Carbon Monoxide and other toxic fumes may be given off. |                       |                             |
| Hazardous Polymerization   | May Occur             | Conditions To Avoid<br>NONE |
|  | Will Not Occur<br>YES |                             |

**SECTION VI - HEALTH HAZARD DATA**

|                    |             |       |            |
|--------------------|-------------|-------|------------|
| Route(s) Of Entry: | Inhalation? | Skin? | Ingestion? |
|                    | NO          | YES   | YES        |

Health Hazards (Acute and Chronic)

Conforms to ASTM D-4236

|   |  |                  |                 |
|---|--|------------------|-----------------|
| Carcinogenicity:                                    | NTP?   | IARC Monographs? | OSHA Regulated? |
|   | N/A  | N/A              | N/A             |
| Signs and Symptoms of Exposure                      | N/A  |                  |                 |
| Medical Conditions Generally Aggravated by Exposure | N/A  |                  |                 |
| Emergency and First Aid Procedures                  | Eyes—flush with copious amounts of water and contact a physician<br>Contact with skin—Wash area with soap and water; Ingestion—seek medical attention; |                  |                 |

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

|   |   |
|---|---|
| Steps to Be Taken in Case Material Is Released or Spilled | Contain and place in approved containers.                 |
| Waste Disposal Method                                     | Dispose of per all Local, State, and Federal Regulations. |
| Precautions to Be Taken in Handling and Storing           | Do not store near heat or open flame.                     |
| Other Precautions   | None  |

**SECTION VIII - CONTROL MEASURES**

|  |                      |  |                |     |
|--|----------------------|--|----------------|-----|
| Respiratory Protection (specify Type)  | N/A                  |  |                |     |
| Ventilation                            | Local Exhaust        | When heating, use locally exhausting hood appropriate for the operation. | Special        | N/A |
|  | Mechanical (General) | OKAY   | Other          | N/A |
| Protective Gloves                      | N/A                  |  | Eye Protection | YES |
| Other Protective Clothing or Equipment | N/A                  |  |                |     |

Work/Hygenic Practices  
 Contents will stain most fabrics, use of smocks, gloves, etc to protect personel clothing is suggested. Wash hands and surfaces after use.