

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Rcvd Nov 2001

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved

OMB No. 1218-0072 407347/348-700



IDENTITY (As Used on Label and List)
SPEEDBALL Screen Drawing Fluid (4531 & 4571)

My 4571
11-28-01

Section I

Manufacturer's Name

SPEEDBALL ART PRODUCTS
2226 SPEEDBALL ROAD
STATESVILLE, NC 28677

Emergency Telephone Number

704-838-1475

Telephone Number for Information

704-838-1475

Date Prepared

6/29/98

Signature of Preparer (optional)

[Handwritten Signature]

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Approved for the AP Seal (Non-Toxic) as per the Art & Creative Materials Institute, Inc. (ACMI). Product labeling conforms to ASTM D4236.				

Note: This product has been evaluated by the Toxicologist only as per intended usage. Do not deviate from intended usage!

V.O.C.: 0

Section III — Physical/Chemical Characteristics

Boiling Point	212°F.	Specific Gravity (H ₂ O = 1)	1.19
Vapor Pressure (mm Hg.)	Unknown	Melting Point	<32°F.
Vapor Density (Air = 1)	less than 1	Evaporation Rate (Butyl Acetate = 1)	less than 1

Solubility in Water
Dilutable

Appearance and Color
Translucent Blue Color with a slight odor

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	Not applicable (N/A)	Flammable Limits	N/A	LEL	N/A	UEL	N/A
---------------------------	----------------------	------------------	-----	-----	-----	-----	-----

Extinguishing Media
N/A

Special Fire Fighting Procedures
wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards
Material can spatter above 212°F. Film can burn.

Stability	Unstable	X	Conditions to Avoid
	Stable		

Onset of decomposition is 350°F.

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts Oxides of carbon and nitrogen.

Hazardous Polymerization	May Occur	X	Conditions to Avoid
	Will Not Occur		

N/A

Section VI — Health Hazard Data

Route(s) of Entry: N/A Inhalation? Skin? Ingestion?

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures Contact with eyes may cause mild irritation: Flush with water.

Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled
 Floor may be slippery; use care to avoid falling. No special handling required under normal use conditions. For large quantities (quart or more), transfer to containers for recovery or disposal and keep out of municipal sewers & open bodies of water.

Waste Disposal Method
 No special handling required under normal use conditions. Incinerate large quantities (quart or more) at a permitted facility according to local, state & Fed. regulation

Precautions to Be Taken in Handling and Storing
 Keep from freezing - product may coagulate.

Other Precautions N/A

Section VIII — Control Measures

Respiratory Protection (Specify Type)
 None required with adequate ventilation & normal operating conditions.

Ventilation	Local Exhaust	Adequate	Special
	Mechanical (General)		Other

Protective Gloves: Impervious
 Eye Protection: Safety glasses

Other Protective Clothing or Equipment N/A

Work Hygienic Practices
 Use protective cream where excessive skin contact is likely.