

Rcvd Feb 2002
ACTIVA PRODUCTS, INC.
P.O. Box 1296
Marshall, TX 75670
Phone: (903) 938-2224
Fax: (903) 938-3899

Product Name: Celluclay
Date: January 2001

MATERIAL SAFETY DATA SHEET

651-9016/350075

SECTION 1 - MANUFACTURER'S INFORMATION

EMERGENCY PHONE NUMBER
(978-692-9300 (Day))

Trade Name: Celluclay

Chemical Name: N/A

Manufacturer's Name: Activa Products, Inc. (978) 692-9300

Address: P.O. Box 472 Westford MA 01996

SECTION 2 - INGREDIENTS INFORMATION

	%	TLV	PEL	UNITS
Product consists of:				
Gypsum	100	10*	15*	MG/M ³
Starch		10*	15*	MG/M ³
Printed clay coat sulfite paper -(as Cellulose (paper fiber))		10*	15*	MG/M ³
Perlite		**	50	MPPCF
Sodium benzoate		NE	NE	

*TLV and PEL are as nuisance particulate,
total dust.

**TLV-10 mg/m³

SECTION 3 – PHYSICAL DATA

Boiling Point: (°F)	NA	Specific Gravity: (H ₂ O=1)	>60
Vapor Pressure:(MM Hg.)	N/A	Percent Volatile	
		By volume (%)	NA
Vapor Density: (AIR-1)	N/A	pH	NA
Solubility in water:	Appreciable	Evaporation rate:	NA

Appearance and Odor: Greyish powder; odorless

SECTION 4 – FIRE AND EXPLOSION HAZARD DATA

		LEL	UEL
Flash Point (Method used)	None	NE	NE
Extinguishing Media	Water		
Special Fire Fighting Procedures	No special procedures required.		
Unusual Fire and Explosion Hazards	Dust clouds will present a fire hazard when exposed to heat or flame.		

SECTION 5 – HEALTH HAZARD INFORMATION

Symptoms/Effects of Overexposure Inhalation of dust may cause respiratory annoyance. Prolonged contact may cause mild skin rash in sensitive individuals. Eye contact may cause watering.

FIRST AID

Eyes Flush eyes with large amounts of water. Get medical attention if irritation persists.

Skin Wash thoroughly with soap and water. Get medical attention if irritation persists.

SECTION 9 – SPECIAL PRECAUTIONS

Store in dry area. This product does not contain any carcinogens (at 0.1% or greater) as defined by IARC, NTP, or OSHA.