

PRODUCT SAFETY DATASHEET

Page 1 of 4
Alkaline Batteries
March 2015**PRODUCT SAFETY DATA SHEET****PRODUCT NAME:** Eveready / Energizer Battery**Type No.:****Volts:****TRADE NAMES:** ENERGIZER, ENERGIZER e², INDUSTRIAL ZMA, HERCULES, EVEREADY, WONDER**Approximate Weight:****CHEMICAL SYSTEM:** Alkaline Manganese Dioxide-Zinc**Designed for Recharge:** No

Energizer has prepared copyrighted Product Safety Datasheets to provide information on the different Eveready/Energizer battery systems. Batteries are articles as defined under the GHS and exempt from GHS classification criteria (Section 1.3.2.1.1 of the GHS). The information and recommendations set forth herein are made in good faith, for information only, and are believed to be accurate as of the date of preparation. However, ENERGIZER BATTERY MANUFACTURING, INC. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM REFERENCE ON IT.

SECTION 1 - MANUFACTURER INFORMATIONEnergizer Battery Manufacturing, Inc.
25225 Detroit Rd.
Westlake, OH 44145Telephone Number for Information:
800-383-7323 (USA / CANADA)

Date Prepared: March 2015

SECTION 2 – HAZARDS IDENTIFICATION**GHS classification:** N/A**Signal Word:** N/A**Hazard Classification:** N/A

Under normal conditions of use, the battery is hermetically sealed.

Ingestion: Swallowing a battery can be harmful. Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.**Inhalation:** Contents of an open battery can cause respiratory irritation.**Skin Contact:** Contents of an open battery can cause skin irritation and/or chemical burns.**Eye Contact:** Contents of an open battery can cause severe irritation and chemical burns.**SECTION 3 - INGREDIENTS****IMPORTANT NOTE:** The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Graphite (CAS# 7782-42-5)	15 mg/m ³ TWA (total dust) 5 mg/m ³ TWA (respirable fraction)	2 mg/m ³ TWA (respirable fraction)	2-6
Manganese Dioxide (CAS# 1313-13-9)	5 mg/m ³ Ceiling (as Mn)	0.2 mg/m ³ TWA (as Mn)	30-45
Potassium Hydroxide (CAS# 1310-58-3)	None established	2 mg/m ³ Ceiling	4-8
Zinc (CAS# 7440-66-6)	15 mg/m ³ TWA PNOR* (total dust) 5 mg/m ³ TWA PNOR* (respirable fraction)	10 mg/m ³ TWA PNOC** (inhalable particulate) 3 mg/m ³ TWA PNOC** (respirable particulate)	12-25

Non-Hazardous Components			
Steel (iron CAS# 65997-19-5)	None established	None established	18-22
Water, Paper, Plastic and Other	None established	None established	Balance

* PNOR: Particulates not otherwise regulated

**PNO: Particulates not otherwise classified

SECTION 4 – FIRST AID MEASURES

Ingestion: Do not induce vomiting or give food or drink. Seek medical attention immediately. CALL NATIONAL BATTERY INGESTION HOTLINE for advice and follow-up (202-625-3333) collect day or night.

Inhalation: Provide fresh air and seek medical attention.

Skin Contact: Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

Eye Contact: Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

To cleanup leaking batteries:

Ventilation Requirements: Room ventilation may be required in areas where there are open or leaking batteries.

Eye Protection: Wear safety glasses with side shields if handling an open or leaking battery.

Gloves: Use neoprene or natural rubber gloves if handling an open or leaking battery.

Battery materials should be collected in a leak-proof container.

SECTION 7 - HANDLING AND STORAGE

Storage: Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life.

Mechanical Containment: If potting or sealing the battery in an airtight or watertight container is required, consult your Energizer Battery Manufacturing, Inc. representative for precautionary suggestions. Batteries normally evolve hydrogen which, when combined with oxygen from the air, can produce a combustible or explosive mixture unless vented. If such a mixture is present, short circuits, high temperature, or static sparks can cause an ignition.

Do not obstruct safety release vents on batteries. Encapsulation (potting) of batteries will not allow cell venting and can cause high pressure rupture.

Handling: Accidental short circuit for a few seconds will not seriously affect the battery. Prolonged short circuit will cause the battery to lose energy, and can cause the safety release vent to open. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, metal covered tables or metal belts used for assembly of batteries into devices.

If soldering or welding to the battery is required, consult your Energizer Battery Manufacturing, Inc. representative for proper precautions to prevent seal damage or short circuit.

Charging: This battery is manufactured in a charged state. It is not designed for recharging. Recharging can cause battery leakage or, in some cases, high pressure rupture. Inadvertent charging can occur if a battery is installed backwards.

Labeling: If the Eveready / Energizer Battery label or package warnings are not visible, it is important to provide a package and/or device label stating:

WARNING: do not install backwards, charge, put in fire, or mix with other battery types. May explode or leak causing injury.

Replace all batteries at the same time.

Where accidental ingestion of small batteries is possible, the label should include:

Keep away from small children. If swallowed, promptly see doctor; have doctor phone (202) 625-3333 collect.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: Not necessary under normal conditions.

Respiratory Protection: Not necessary under normal conditions.

Eye Protection: Not necessary under normal conditions.

Gloves: Not necessary under normal conditions.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid object
Upper Explosive Limits:	Not applicable for an Article
Lower Explosive Limits	Not applicable for an Article
Odor	No odor
Vapor Pressure (mm Hg @ 25°C)	Not applicable for an Article
Odor Threshold	No odor
Vapor Density (Air = 1)	Not applicable for an Article
pH	Not applicable for an Article
Density (g/cm ³)	2.0 – 3.0
Melting point/Freezing Point	Not applicable for an Article
Solubility in Water (% by weight)	Not applicable for an Article
Boiling Point @ 760 mm Hg (°C)	Not applicable for an Article
Flash Point	Not applicable for an Article
Evaporation Rate (Butyl Acetate = 1)	Not applicable for an Article
Flammability	Not applicable for an Article
Partition Coefficient	Not applicable for an Article
Auto-ignition Temperature	Not applicable for an Article
Decomposition Temperature	Not applicable for an Article
Viscosity	Not applicable for an Article

SECTION 10 – STABILITY AND REACTIVITY

Alkaline batteries do not meet any of the criteria established in 40 CFR 261.2 for reactivity.

SECTION 11 – TOXICOLOGICAL INFORMATION

Under normal conditions of use, alkaline batteries are non-toxic.

SECTION 12 – ECOLOGICAL INFORMATION

Issues such as ecotoxicity, persistence and bioaccumulation are not applicable for articles.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable federal, state and local regulations. Appropriate disposal technologies include incineration and land filling.

SECTION 14 – TRANSPORT INFORMATION

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for Energizer alkaline batteries has been designed to be compliant with these regulatory concerns.

Alkaline batteries (sometimes referred to as "Dry cell" batteries) are not listed as dangerous goods under the ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road, the IMDG International Maritime Dangerous Goods Code, UN Dangerous Good Regulations, IATA Dangerous Goods Regulations, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions.

Regulatory Body	Special Provisions
ADR	Not regulated
IMDG	Not regulated
UN	Not regulated
US DOT	49 CFR 172.102 Provision 130
IATA	A123
ICAO	Not regulated

All Energizer alkaline batteries are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provisions listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

SECTION 15 - REGULATORY INFORMATION

Batteries marketed by Energizer Battery Manufacturing, Inc. are not classified as dangerous goods by the US Department of Transportation or the major international regulatory bodies and are therefore not regulated.

SARA/TITLE III - As an article, this battery and its contents are not subject to the requirements of the Emergency Planning and Community Right-To-Know Act.

SECTION 16 - OTHER INFORMATION

None.

PRODUCT SAFETY DATA SHEET

PRODUCT NAME: Eveready Battery

Type No.: **Volts:**

TRADE NAMES: CLASSIC; SUPER HEAVY DUTY; INDUSTRIAL; HERCULES

Approximate Weight:

CHEMICAL SYSTEM: Carbon Zinc

Designed for Recharge: No

Energizer has prepared copyrighted Product Safety Datasheets to provide information on the different Eveready/Energizer battery systems. Batteries are articles as defined under the GHS and exempt from GHS classification criteria (Section 1.3.2.1.1 of the GHS). The information and recommendations set forth herein are made in good faith, for information only, and are believed to be accurate as of the date of preparation. However, ENERGIZER BATTERY MANUFACTURING, INC. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM REFERENCE ON IT.

SECTION 1 - MANUFACTURER INFORMATION

Energizer Battery Manufacturing, Inc.
25225 Detroit Rd.
Westlake, OH 44145

Telephone Number for Information:
800-383-7323 (USA / CANADA)

Date Prepared: March 2015

SECTION 2 – HAZARDS IDENTIFICATION

GHS classification: N/A

Signal Word: N/A

Hazard Classification: N/A

Under normal conditions of use, the battery is hermetically sealed.

Ingestion: Swallowing a battery can be harmful. Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.

Inhalation: Contents of an open battery can cause respiratory irritation.

Skin Contact: Contents of an open battery can cause skin irritation and/or chemical burns.

Eye Contact: Contents of an open battery can cause severe irritation and chemical burns.

SECTION 3 - INGREDIENTS

IMPORTANT NOTE: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Acetylene Black (CAS# 1333-86-4)	3.5 mg/m ³ TWA (as carbon black)	3.5 mg/m ³ TWA (as carbon black)	3-7
Ammonium Chloride (CAS# 12125-02-9)	None established	10 mg/m ³ TWA (fume) 20 mg/m ³ STEL (fume)	0-10
Manganese Dioxide (CAS# 1313-13-9)	5 mg/m ³ CEILING (as Mn)	0.2 mg/m ³ TWA (as Mn)	15-31
Zinc (CAS# 7440-66-6)	15 mg/m ³ TWA PNOR* (total dust) 5 mg/m ³ TWA PNOR* (respirable fraction)	10 mg/m ³ TWA PNOC** (inhalable particulate) 3 mg/m ³ TWA PNOC** (respirable particulate)	7-42

Zinc Chloride (CAS# 7646-85-7)	1 mg/m ³ TWA (fume)	1 mg/m ³ TWA (fume) 2 mg/m ³ STEL (fume)	2-10
Non-Hazardous Components Steel (Iron CAS #65997-19-5)	None established	None established	23-28
Water, Paper, Plastic and Other	Non established	Non established	Balance

* PNOR: Particulates not otherwise regulated

**PNOC: Particulates not otherwise classified

SECTION 4 – FIRST AID MEASURES

Ingestion: Do not induce vomiting or give food or drink. Seek medical attention immediately. CALL NATIONAL BATTERY INGESTION HOTLINE for advice and follow-up (202-625-3333) collect day or night.

Inhalation: Provide fresh air and seek medical attention.

Skin Contact: Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

Eye Contact: Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

To cleanup leaking batteries:

Ventilation Requirements: Room ventilation may be required in areas where there are open or leaking batteries.

Eye Protection: Wear safety glasses with side shields if handling an open or leaking battery.

Gloves: Use neoprene or natural rubber gloves if handling an open or leaking battery.

Battery materials should be collected in a leak-proof container.

SECTION 7 - HANDLING AND STORAGE

Storage: Store in a cool, well ventilated area. Elevated temperatures can result in shortened battery life.

Mechanical Containment: If potting or sealing the battery in an airtight or watertight container is required, consult your Energizer Battery Manufacturing, Inc. representative for precautionary suggestions. Batteries normally evolve hydrogen which, when combined with oxygen from the air, can produce a combustible or explosive mixture unless vented. If such a mixture is present, short circuits, high temperature, or static sparks can cause an ignition.

Do not obstruct safety release vents on batteries. Encapsulation (potting) of batteries will not allow cell venting and can cause high pressure rupture.

Handling: Accidental short circuit for a few seconds will not seriously affect the battery. Prolonged short circuit will cause the battery to lose energy, and can cause the safety release vent to open. Sources of short circuits include jumbled batteries in bulk containers, metal jewelry, metal covered tables or metal belts used for assembly of batteries into devices.

If soldering or welding to the battery is required, consult your Energizer Battery Manufacturing, Inc. representative for proper precautions to prevent seal damage or short circuit.

Charging: This battery is manufactured in a charged state. It is not designed for recharging. Recharging can cause battery leakage or, in some cases, high pressure rupture. Inadvertent charging can occur if a battery is installed backwards.

Labeling: If the Eveready Battery label or package warnings are not visible, it is important to provide a package and/or device label stating:

WARNING: do not install backwards, charge, put in fire, or mix with other battery types. May explode or leak causing injury.
Replace all batteries at the same time.

Where accidental ingestion of small batteries is possible, the label should include:

Keep away from small children. If swallowed, promptly see doctor; have doctor phone (202) 625-3333 collect.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: Not necessary under normal conditions.

Respiratory Protection: Not necessary under normal conditions.

Eye Protection: Not necessary under normal conditions.

Gloves: Not necessary under normal conditions.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Solid object
Upper Explosive Limits:	Not applicable for an Article
Lower Explosive Limits	Not applicable for an Article
Odor	No odor
Vapor Pressure (mm Hg @ 25°C)	Not applicable for an Article
Odor Threshold	No odor
Vapor Density (Air = 1)	Not applicable for an Article
pH	Not applicable for an Article
Density (g/cm ³)	2.0 – 3.0
Melting point/Freezing Point	Not applicable for an Article
Solubility in Water (% by weight)	Not applicable for an Article
Boiling Point @ 760 mm Hg (°C)	Not applicable for an Article
Flash Point	Not applicable for an Article
Evaporation Rate (Butyl Acetate = 1)	Not applicable for an Article
Flammability	Not applicable for an Article
Partition Coefficient	Not applicable for an Article
Auto-ignition Temperature	Not applicable for an Article
Decomposition Temperature	Not applicable for an Article
Viscosity	Not applicable for an Article

SECTION 10 – STABILITY AND REACTIVITY

Carbon zinc batteries do not meet any of the criteria established in 40 CFR 261.2 for reactivity.

SECTION 11 – TOXICOLOGICAL INFORMATION

Under normal conditions of use, carbon zinc batteries are non-toxic.

SECTION 12 – ECOLOGICAL INFORMATION

Issues such as ecotoxicity, persistence and bioaccumulation are not applicable for articles.

SECTION 13 – DISPOSAL CONSIDERATIONS

Dispose of in accordance with all applicable federal, state and local regulations. Appropriate disposal technologies include incineration and land filling.

SECTION 14 – TRANSPORT INFORMATION

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for Energizer alkaline batteries has been designed to be compliant with these regulatory concerns.

Carbon zinc batteries (sometimes referred to as "Dry cell" batteries) are not listed as dangerous goods under the ADR European Agreement Concerning the International Carriage of Dangerous Goods by Road, the IMDG International Maritime Dangerous Goods Code, UN Dangerous Good Regulations, IATA Dangerous Goods Regulations, ICAO Technical Instructions and the U.S. hazardous materials regulations (49 CFR). These batteries are not subject to the dangerous goods regulations provided they meet the requirements contained in the following special provisions.

Regulatory Body	Special Provisions
ADR	Not regulated
IMDG	Not regulated
UN	Not regulated
US DOT	49 CFR 172.102 Provision 130
IATA	A123
ICAO	Not regulated

All Energizer or Eveready carbon zinc batteries are packed in such a way to prevent short circuits or the generation dangerous quantities of heat and meet the special provisions listed above. In addition, the IATA Dangerous Goods Regulations and ICAO Technical Instructions require the words "not restricted" and the Special Provision number A123 be provided on the air waybill, when an air waybill is issued.

SECTION 15 - REGULATORY INFORMATION

Batteries marketed by Energizer Battery Manufacturing, Inc. are not classified as dangerous goods by the US Department of Transportation or the major international regulatory bodies and are therefore not regulated.

SARA/TITLE III - As an article, this battery and its contents are not subject to the requirements of the Emergency Planning and Community Right-To-Know Act.

SECTION 16 - OTHER INFORMATION

None.

Safety Data Sheet**Section 1: Identification of the Substance/Mixture and of the Company/Undertaking****1.1 Product identifier****Product Name**

- **Common Salt without Additives**

Synonyms

- All Purpose Natural Sea Salt; All Purpose Purex Salt; Bunny Spool (Plain Salt); California Pure Coarse Sea Salt; California Pure Fine Sea Salt; California Pure Medium Sea Salt; Canning & Pickling Salt; Commercial Grade, Water Softening Pellets; Culinox 999 Chemical Grade Salt; Culinox 999 Fine Salt; Culinox 999 Food Grade Salt; Evaporated Granulated Salt; Evaporated Salt Pellets; Feed Mixing Salt, Northern Rock, F & R; Fine Mixing Salt; H.G. Blending Salt; Hay & Stock Salt, F&R; Industrial Crude Solar Salt; KD Crude Solar Salt; Kleer Fine Salt; Kleer Granulated Salt; Mill Run Salt; Natural Coarse Sea Salt; Northern Fine +20 Rock Salt; Plain Salt Block; Plain Salt Brick; Pool Salt; Professional's Choice Pool Salt; Purex Salt; Purex Select Salt; Reagent Grade Sodium Chloride; Refined Sea Salt; Rock Pretzel Salt; Rock Salt for Making Ice Cream; Safe-T-Salt (bagged w/o YPS); Sea Salt Grinder; Sea Salt Grinder Reill; Select Extra Coarse Rock Salt; Service Pack Salt (all); Ship n' Shore Rock Salt; Solar Salt Water Softening Crystals; Stock Salt; USP Sodium Chloride; Valu-Soft Solar Salt; Water Softening Salt (Undried) Coarse; Water Softening Salt (Undried) Extra Coarse; White Crystal Brine Block (50 lb); White Crystal Rock Salt (all); White Crystal Solar Salt (all); White Crystal Water Softening Solar Salt (all); White Pretzel Salt; Dried Coarse Salt

CAS Number

- 7647-14-5

Product Code

- MSDS Code: 100

1.2 Relevant identified uses of the substance or mixture and uses advised against**Relevant identified use(s)**

- Food, Chemical and Drug Processing; Pharmaceuticals; Water Conditioning; Ice Control; Chemical Feedstock – see product data sheets for more information

1.3 Details of the supplier of the safety data sheet**Manufacturer**

- Morton Salt, Inc.
123 N. Wacker Drive
Chicago, IL 60606
United States

saltinfo@mortonsalt.com

Telephone (General) • 312-807-2000

1.4 Emergency telephone number**Manufacturer**

- 312-807-2000

Section 2: Hazards Identification**EU/EEC**

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]
According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

- CLP • Classification criteria not met
DSD/DPD • Classification criteria not met

2.2 Label Elements

- CLP
Hazard statements • No label element(s) specifically required
DSD/DPD
Risk phrases • No label element(s) specifically required

2.3 Other Hazards

- CLP • According to Regulation (EC) No. 1272/2008 (CLP) this material is not considered hazardous.
DSD/DPD • This product is not considered dangerous under the European Directive 67/548/EEC

United States (US)

According to OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

- OSHA HCS 2012 • Classification criteria not met

2.2 Label elements

- OSHA HCS 2012
Hazard statements • No label element(s) specifically required

2.3 Other hazards

- OSHA HCS 2012 • This product is not considered hazardous under the U.S. OSHA 29 CFR 1910.1200 Hazard Communication Standard.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

- WHMIS • Classification criteria not met


2.2 Label elements

- WHMIS • No label element(s) specifically required

2.3 Other hazards

- WHMIS • In Canada, the product mentioned above is not considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

2.4 Other information



See Section 12 for Ecological Information.

Section 3 - Composition/Information on Ingredients

3.1 Substances

Non-Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Sodium chloride	CAS:7647-14-5 EC Number:231-598-3	> 99%	Ingestion/Oral-Rat LD50 • 3000 mg/kg	EU DSD/DPD: Not Classified - Criteria not met EU CLP: Not Classified - Criteria not met OSHA HCS 2012: Not Classified - Criteria not met	May contain small quantities of naturally occurring calcium and magnesium salts

3.2 Mixtures

- Material does not meet the criteria of a mixture in accordance with Regulation (EC) No 1272/2008.

See Section 11 for Toxicological Information.

Section 4 - First Aid Measures

4.1 Description of first aid measures

- Inhalation**
- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.
- Skin**
- IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.
- Eye**
- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Ingestion**
- If large quantities are swallowed, call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

- Suitable Extinguishing Media**
- Material is non-combustible. In case of fire use media as appropriate for surrounding fire.
- Unsuitable Extinguishing Media**
- No data available.

5.2 Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- No unusual fire or explosion hazards known.
- Hazardous Combustion Products**
- No data available

5.3 Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Wear suitable protective clothing, gloves, and eye/face protection.

Emergency Procedures

- Stop leak if you can do it without risk. Keep unauthorized personnel away. Use normal clean up procedures.

6.2 Environmental precautions

- None expected to be necessary if material is used under ordinary conditions and as recommended.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Carefully shovel or sweep up spilled material and place in suitable container.

6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Use good safety and industrial hygiene practices. Wash thoroughly after handling. Keep out of reach of children.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Avoid storage with strong acids and strong oxidizing agents.

Incompatible Materials or Ignition Sources

- Strong oxidizing agents, strong acids.

7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Exposure Limits/Guidelines

- No applicable exposure limits available for product or components.

8.2 Exposure controls

Engineering Measures/Controls

- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values.

Personal Protective Equipment

Pictograms



Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment.

Eye/Face

- Wear safety glasses.

Skin/Body	<ul style="list-style-type: none"> Wear appropriate gloves.
General Industrial Hygiene Considerations	<ul style="list-style-type: none"> Do not get in eyes or on skin or clothing. Handle in accordance with good industrial hygiene and safety practice.
Environmental Exposure Controls	<ul style="list-style-type: none"> Follow best practice for site management and disposal of waste.

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description			
Physical Form	Solid	Appearance/Description	Colorless to white crystalline or compressed block/pellet.
Color	Colorless to White.	Odor	Odorless
Particulate Type	Dust Crystalline	Particulate Size	Variable
Odor Threshold	Data lacking		
General Properties			
Boiling Point	1413 to 1461 C(2575.4 to 2661.8 F)	Melting Point	801 C(1473.8 F)
Decomposition Temperature	Data lacking	pH	7 Approximately
Specific Gravity/Relative Density	2.165 Water=1	Bulk Density	Variable
Water Solubility	Soluble 0.36 g/cc @ 20 C(68 F)	Viscosity	Not relevant
Explosive Properties	Not relevant.	Oxidizing Properties:	Not relevant.
Volatility			
Vapor Pressure	Not relevant	Vapor Density	Not relevant
Evaporation Rate	Not relevant		
Flammability			
Flash Point	Not relevant	UEL	Not relevant
LEL	Not relevant	Autoignition	Not relevant
Flammability (solid, gas)	Not flammable.		
Environmental			
Octanol/Water Partition coefficient	Not relevant		

9.2 Other Information

- No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

- Stable

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Conditions to avoid

- Incompatible materials.

10.5 Incompatible materials

- Strong oxidizing agents, strong acids.

10.6 Hazardous decomposition products

- Will react with strong acids to generate hydrogen chloride and with strong oxidizing agents to generate chlorine gas.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	CAS	Data
Sodium chloride (> 99%)	7647-14-5	Acute Toxicity: ori-rat LD50:3000 mg/kg
GHS Properties		Classification
Acute toxicity		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Aspiration Hazard		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Carcinogenicity		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Germ Cell Mutagenicity		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin corrosion/Irritation		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Skin sensitization		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-RE		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
STOT-SE		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Toxicity for Reproduction		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Respiratory sensitization		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met
Serious eye damage/Irritation		EU/CLP • Classification criteria not met OSHA HCS 2012 • Classification criteria not met

Potential Health Effects

Inhalation

Acute (Immediate)

- Under normal conditions of use, no health effects are expected. Inhalation of dust may cause mild irritation to mucous membranes, nose and throat. Symptoms may include coughing, dryness and sore throat.

Chronic (Delayed)

- No data available.

Skin

Acute (Immediate)

- Under normal conditions of use, no health effects are expected.

Chronic (Delayed)

- No data available.

Eye**Acute (Immediate)**

- Based upon practical use and experience using this product eye irritation is not expected to occur.

Chronic (Delayed)

- No data available.

Ingestion**Acute (Immediate)**

- Ingestion may cause the following symptoms - diarrhea.

Chronic (Delayed)

- No data available.

Key to abbreviations

LD = Lethal Dose

Section 12 - Ecological Information**12.1 Toxicity**

- Material data lacking.

12.2 Persistence and degradability

- Material data lacking.

12.3 Bioaccumulative potential

- Material data lacking.

12.4 Mobility in Soil

- Material data lacking.

12.5 Results of PBT and vPvB assessment

- No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

- No studies have been found.

Section 13 - Disposal Considerations**13.1 Waste treatment methods****Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Not regulated	NDA	NDA	NDA
TDG	NDA	Not regulated	NDA	NDA	NDA
IMO/IMDG	NDA	Not regulated	NDA	NDA	NDA

IATA/ICAO	NDA	Not regulated	NDA	NDA	NDA
-----------	-----	---------------	-----	-----	-----

14.6 Special precautions for user • None known.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code • Not relevant.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • None

State Right To Know				
Component	CAS	MA	NJ	PA
Sodium chloride	7647-14-5	No	No	No

Inventory						
Component	CAS	Canada DSL	Canada NDSL	China	EU EINECS	EU ELNICS
Sodium chloride	7647-14-5	Yes	No	Yes	Yes	No

Inventory (Con't.)				
Component	CAS	Japan ENCS	Korea KECL	TSCA
Sodium chloride	7647-14-5	Yes	Yes	Yes

Canada

Labor

Canada - WHMIS - Classifications of Substances

- Sodium chloride 7647-14-5 > 99% Uncontrolled product according to WHMIS classification criteria

Canada - WHMIS - Ingredient Disclosure List

- Sodium chloride 7647-14-5 > 99% Not Listed

Environment

Canada - CEPA - Priority Substances List

- Sodium chloride 7647-14-5 > 99% Not Listed

Europe

Other

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

- Sodium chloride 7647-14-5 > 99% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

- Sodium chloride 7647-14-5 > 99% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

- Sodium chloride 7647-14-5 > 99% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

- Sodium chloride 7647-14-5 > 99% Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

- Sodium chloride 7647-14-5 > 99% Not Listed

Mexico

Other

Mexico - Hazard Classifications

- Sodium chloride 7647-14-5 > 99% Not Listed

Mexico - Regulated Substances

- Sodium chloride 7647-14-5 > 99% Not Listed

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

- Sodium chloride 7647-14-5 > 99% Not Listed

Environment

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

- Sodium chloride 7647-14-5 > 99% Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

- Sodium chloride 7647-14-5 > 99% Not Listed

United States - Pennsylvania

Labor

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

- Sodium chloride 7647-14-5 > 99% Not Listed

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

- Sodium chloride 7647-14-5 > 99% Not Listed

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

- Sodium chloride 7647-14-5 > 99% Not Listed

15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

Section 16 - Other Information

Last Revision Date ● 18/February 2014

Preparation Date ● 09/August/2012

Disclaimer/Statement of Liability

- The responsibility to provide a safe workplace remains with the user. The user should consider the health hazards and safety information contained herein as a guide and should take those precautions required in an individual operation to instruct employees and develop work practice procedures for a safe work environment. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.

Key to abbreviations

NDA = No data available

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity	Isoamyl Benzoate for Synthesis
Alternate Names	Isoamyl Benzoate for Synthesis

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use	Chemical for synthesis
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Thermco Products, Inc. 10 Millpond Drive, Unit #10 Lafayette, NJ 07848
---------------------	---

Emergency

Customer Service: Thermco Products, Inc.	973.300.9100
---	--------------

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Combustible Liquid;H227 Combustible Liquid.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.
H227 Combustible liquid.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
P280 Wear protective gloves / eye protection / face protection.

[Response]:

No GHS response statements

[Storage]:

P403+235 Store in a well ventilated place. Keep cool.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

Safety Data Sheet

Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
ISOPENTYL BENZOATE CAS Number: 0000094-46-2	100	Not classified	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview	No specific symptom data available. See section 2 for further details.
-----------------	---

5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.
Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Do not inhale vapors/aerosols. Ensure supply of fresh air in enclosed rooms.

Safety Data Sheet

Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



Hazardous decomposition: No hazardous decomposition data available.
Keep away from heat / sparks / open flames / hot surfaces - No smoking.

5.3. Advice for fire-fighters

Special risks:

Combustible. Vapors heavier than air.
Forms explosive mixtures with air on intense heating.
Development of hazardous combustion gases or vapors possible in the event of fire.

Special protective equipment for fire fighting:

Do not stay in dangerous zone without self-contained breathing apparatus.
Do not allow run off water and contaminants from fire fighting to enter drains or water ways.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).
Do not inhale vapors/aerosols. Ensure supply of fresh air in enclosed rooms.

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.
Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Do not inhale vapors/aerosols. Ensure supply of fresh air in enclosed rooms.
Take up with liquid-absorbent material (e.g. Chemizorb). Forward for disposal. Clean up affected area.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible liquids.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store in a cool dry area, away from heat, sparks and open flame. Keep containers sealed when not in use. Store out of direct sunlight.

Incompatible materials: Strong oxidizing agents

Tightly closed. At +15C to +25C.

Safety Data Sheet

Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000094-46-2	ISOPENTYL BENZOATE	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000094-46-2	ISOPENTYL BENZOATE	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Protective safety glasses required

Skin

Butyl rubber gloves
 Layer thickness: 0.7 mm
 Breakthrough time: >240 min

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

Safety Data Sheet

Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



9. Physical and chemical properties

Appearance	Colorless Liquid
Odor	Almost Odorless
Odor threshold	Not Measured
pH	NA
Melting point / freezing point	NA
Initial boiling point and boiling range	260 C
Flash Point	89 C
Evaporation rate (Ether = 1)	NA
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: NA Upper Explosive Limit: NA
Vapor pressure (Pa)	NA
Vapor Density	NA
Density	0.99 g/cm ³ (@20C)
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	NA
Decomposition temperature	NA
Viscosity (cSt)	NA
VOC %	NA
Log Pow	4.15 (experimental) (Lit.)

9.2. Other information

No other relevant information.

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Forms explosive mixtures with air on intense heating.

Safety Data Sheet

Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



10.5. Incompatible materials

Strong Oxidizing agents.

10.6. Hazardous decomposition products

No hazardous decomposition data available.

11. Toxicological information

Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
ISOPENTYL BENZOATE - (94-46-2)	6330.00, Rat - Category: NA	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Safety Data Sheet

Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



12. Ecological information

12.1. Toxicity

Do not allow product to enter water, wastewater or soil! See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
ISOPENTYL BENZOATE - (94-46-2)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

An appreciable bioaccumulation potential is to be expected ($\log P_{o/w} > 3$)

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA) All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification B3

US EPA Tier II Hazards

Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): No

Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:
(No Product Ingredients Listed)

EPCRA 302 Extremely Hazardous :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals:
(No Product Ingredients Listed)

Proposition 65 - Carcinogens (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Female Repro Toxins (>0.0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0.0%):
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :
(No Product Ingredients Listed)

Penn RTK Substances (>1%) :
(No Product Ingredients Listed)

Safety Data Sheet
Isoamyl Benzoate for Synthesis

SDS Revision Date:

12/09/2014



16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is: not applicable

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

Disclaimer: This information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Document



Brands That Matter

Office Products Group

MATERIAL SAFETY DATA SHEET

MSDS # 3000

Section One: Identification

Newell Rubbermaid, Inc. (Sanford L.P.)
2707 Butterfield Road
Oak Brook, IL 60523 USA
800-323-0749 or 630-481-2000

EMERGENCY MEDICAL NUMBER:

888-786-0972

Product Name: Sharpie Fine Point Marker, Sharpie Ultra Fine Point Marker, Sharpie Extra Fine Marker, Sharpie Chisel Tip Marker, Sharpie Twin Tip Marker, Super Sharpie Marker, Super Sharpie Twin Tip Marker, Sharpie Mini Fine Point Marker, Sharpie Micro Marker, Sharpie Grip Marker, Sharpie Retractable Fine Point Marker, Sharpie Magnum Marker, Sharpie King Size Marker, Sharpie Liquid Tip Marker.

Colors: All Colors

NewellRubbermaid, Inc (Sanford L.P.) is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 and is labeled with the AP Non Toxic Seal. Products bearing the AP Approved Product Seal of The Art and Creative Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute Toxicology Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans, or to cause acute toxicity or chronic health problems.

Section Two: Hazard Identification

Not Hazardous under normal use conditions. Not for use on skin. Do not ingest. Contact with eyes may cause irritation.

Section Three: Composition

Dyes

Pigments

Solvent Mixture: Butanol (71-36-3), Propanol (71-23-8), Diacetone Alcohol (123-42-2), Ethanol (64-17-5)

Section Four: First Aid Measures

Inhalation: Remove source of irritation. If symptoms persist seek medical attention
Skin Contact: Wash with soap and water. If irritation persists seek medical attention.
Eye Contact: Rinse eyes with water, if irritation persists seek medical attention.
Ingestion: If symptoms occur seek medical attention.

Section Five: Fire Fighting Measures

Flash Point: N/A
Extinguishing Media: As appropriate for surrounding area.
Special Fire Fighting Measures: N/A
Hazardous combustion products: N/A

Section Six: Accidental Release Measures

In Case of Spill or Accidental Release: Wipe up with absorbent material.

Section Seven: Handling and Storage

Handling: Do not shake marker.
Storage: Keep cap on marker when not in use.

Section Eight: Exposure Controls and Personal Protection

Eye Protection: None under normal use conditions.
Clothing: None under normal use conditions.
Respirator: None under normal use conditions.



Brands That Matter

Office Products Group

MATERIAL SAFETY DATA SHEET

MSDS # 3000

Section Nine: Physical and Chemical Properties

Bolling Point: N/A
Specific Gravity: N/A
Vapor Pressure: N/A
Solubility in Water: N/A
Evaporation Rate: N/A
Appearance/Odor: Marker/Alcohol (ink)

Section Ten: Stability and Reactivity

Stability: N/A
Conditions to Avoid: Avoid exposure to heat, flame or other sources of ignition.
Chemical Incompatibility: N/A
Hazardous Polymerization: N/A

Section Eleven: Toxicological Information

See Section Two: Hazard Identification for any hazards

Section Twelve: Ecological Information

Not available

Section Thirteen: Disposal Considerations

Dispose of in accordance with all Federal, State, and Local Regulations.

Section Fourteen: Transport Information

DOT: Not available
IATA: Not available
IMO: Not available

Section Fifteen: Regulatory Information

United States: All components in this product are listed on or exempt from reporting under the Federal Toxic Substances Control Act (TSCA).

Section Sixteen: Other Information

Table with 2 columns: HMIS Code, Health, Flammability, Reactivity, Personal Protection. Values are N/A.

0=Minimal / 4 = Severe

NewellRubbermaid, Inc has been advised by Counsel that the OSHA Hazard Communication Standard and the Health Canada Workplace Hazardous Materials Information Standard do not apply to the Sanford Product described in this Material Safety Data Sheet. The reasons for the exemptions are contained in 29 CFR 1910.1200(b)(6)(ix) as amended Sept 14, 2009 per the Code of Federal Regulations and also Canadian Hazardous Products Act part 12 section (f) as amended June 1, 2009. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by nor is this MSDS meant to comply with all requirements of the hazard communication standards.

Hazard Communication Compliance Declaration

Newell-Rubbermaid (NWL) writing instruments comply with U.S. OSHA GHS Hazard Communication Standard of 29 CFR section 1910.1200 (OSHA HazCom 2012) by virtue of exemption as 'articles' and as 'consumer products' per 29 CFR section 1910.1200(b)(6)(v) and (ix). Therefore, GHS Safety Data Sheets are not required for our writing instruments.

An 'article' is defined in Section 1910.1200(c) "as a manufactured item other than a fluid or particle:

- Which is formed to a specific shape or design during manufacture;
- Which has end use function(s) dependent in whole or in part on its shape or design during end use; and
- Which, under normal conditions of use, does not release other than very small (minute or trace) amounts of a hazardous chemical and does not pose a physical hazard or health risk to employees."

The 'consumer product' exemption in 29 C.F.R. section 1910.1200(b)(6)(ix) states that:

- Any consumer product or hazardous substance, as those terms are defined in the Consumer Product Safety Act (15 U.S.C. 2051 et seq.) and Federal Hazardous Substances Act (15 U.S.C. 1261 et seq.) respectively, where the employer can show that it is used in the workplace for the purpose intended by the chemical manufacturer or importer of the product, and the use results in a duration and frequency of exposure which is not greater than the range of exposures that could reasonably be experienced by consumers when used for the purpose intended.

OSHA has consistently taken the position, in various rulemaking documents and interpretation letters, "most office products (such as pens, pencils, adhesive tape) to be exempt under the provisions of the rule, either as articles or as consumer products." Markers also fall into these exempted categories. This position is cited currently on [OSHA's website](#) in a letter from OSHA Assistant Secretary John A. Pendergrass to U.S. Congressman Jim Bunning. These examples are cited again in OSHA's FAQs on the [Hazard Communication Standard](#) which further reinforces that Newell-Rubbermaid writing products are exempt from Hazard Communication requirements, specifically GHS Safety Data Sheet documentation.


A non-exhaustive list is provided below of Newell-Rubbermaid writing instruments that qualify as 'articles' and 'consumer products' that are exempt from GHS Safety Data Sheet requirements:

- Prismacolor Premier Colored Pencils and Sharpeners
- Prismacolor Nupastels and Art Stix and Erasers
- Sharpie Permanent Markers
- Sharpie Pens
- Sharpie Highlighters (Clearview, Accent, etc)
- Paper Mate Pens (InkJoy, FlexGrip, Replay, etc)
- Paper Mate Mechanical Pencils
- Paper Mate Flair Pens
- Paper Mate Pearl Erasers
- Paper Mate Replay Premium Erasable Pens
- Expo Dry Erase Markers
- Expo Whiteboard Cleaner Wipes
- Expo Learning Boards
- Liquid Paper Correction Pens
- Liquid Paper Dryline Correction Tape
- Parker Fountain Pens
- Waterman Fountain Pens
- Rotring Tikky Ballpoint Pens
- Woodcase Pencils (Mongol, Mirado, etc)
- uni-ball pens

3500 Lacey Road | Downers Grove, IL | Phone +1 (630)-829-2500 | www.newellrubbermaid.com



IRWIN



LEVOLOR



Aprica