

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard Must Be
 Consulted for Specific Requirements
 IDENTITY (As Used on Label and List)
 Prang Semimoist Water Colors

Rec'd Jan 2002

Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

SECTION I

Manufacturer's Name DIXON TICONDEROGA Address (Number, Street, City, State, and ZIP) 1706 HAYES AVENUE SANDUSKY, OHIO 44870	Emergency Telephone Number	(419) 625-9545
	Telephone Number for Information	(419) 625-9545
	Date Prepared	12/19/01
	Signature of Preparer (optional)	

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended %Optional
--	----------	-----------	---------------------------------------

Products bearing the CP Certified Products or AP Approved Products seals of the Art and Creative Materials Institute, Inc. are certified in a program of Toxicological evaluation by a Medical expert, subject to review by the Institute's Toxicological Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans or cause acute or chronic health problems.

CONFORMS TO ASTM-4236

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	NA	Specific Gravity (B20 = 1)	NA
Vapor Pressure (mm Hg)	NA	Melting Point	N/A
Vapor Density (Air=1)	NA	Evaporation Rate (Butyl Acetate = 1)	NA
Solubility In Water	Miscible with water (a water-based product with insolubles)		
Appearance and Odor	Assorted colored cakes, no odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	N/A	Flammable Limits	N/A	LEL	N/A	URL	N/A
---------------------------	-----	------------------	-----	-----	-----	-----	-----

Extinguishing Media
 Water Spray, Foam, CO2

Special Fire Fighting Procedures
 Containers may be subject to ignition by fire and may release toxic or other irritating gases

Unusual Fire and Explosion Hazards
 A self contained breathing apparatus should be used for this exposure.

(Reproduce Locally) OSHA 174, SEPT. 1985

SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions To Avoid	NONE
	Stable		

Incompatibility (Materials To Avoid)
 NONE

Hazardous Decomposition or Byproducts
 As with all burning organic matter, Carbon Monoxide and other toxic fumes may be given off.

Hazardous Polymerization	May Occur	Conditions To Avoid	NONE
	Will Not Occur		

SECTION VI - HEALTH HAZARD DATA

Route(s) Of Entry:	Inhalation?	NO	Skin?	YES	Ingestion?	YES
--------------------	-------------	----	-------	-----	------------	-----

Health Hazards (Acute and Chronic)

Conforms to ASTM D-4236

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	N/A	N/A	N/A
Gases and Symptoms of Exposure			
N/A			
Medical Conditions Generally Aggravated by Exposure			
N/A			
Emergency and First Aid Procedures			
Eyes—flush with copious amounts of water and contact a physician			
Contact with skin—Wash area with soap and water; Ingestion—seek medical attention;			

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled	Contain and place in approved containers.
Waste Disposal Method	Dispose of per all Local, State, and Federal Regulations.
Precautions to Be Taken in Handling and Storing	Do not store near heat or open flame.
Other Precautions	None

SECTION VIII - CONTROL MEASURES

Respiratory Protection (specify Type)			
N/A			
Ventilation	Local Exhaust	OKAY	Special
	Mechanical (General)	OKAY	Other
Protective Gloves	N/A		Eye Protection
			YES
Other Protective Clothing or Equipment			
N/A			
Work/Hygiene Practices			
Contents will stain most fabrics, use of smocks, gloves, etc to protect personnel clothing is suggested. Wash hands and surfaces after use.			