

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910 1200 Standard must be consulted for specific requirements

Art-Office School-Craft Charcoal-Graphite Pastels-Colored

U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No 1218-0072



320 125/373787

IDENTITY (As Used on Label and List)
All wood cased pencil products

Note: Blank spaces are not permitted if any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Rec'd March 2002

Manufacturer's Name
GENERAL PENCIL CO.

Emergency Telephone Number
1-800-557-0734

Address (Number, Street, City, State, and ZIP Code)
67 Fleet St. Jersey City N.J 07306

Telephone Number for Information
1-201-653-5351 --- 1-415-369-4889

California--3168 Bay Rd. Bpx 5311
Redwood City, CA 94063

Date Prepared
Revised 4/15/92

Signature of Preparer (optional)
Sam Wessner

Section II -- Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Name(s))	OSHA PEL	ACGIH TLV	Recommended	% (optional)
---	----------	-----------	-------------	--------------

N/A-----Pencil products bearing the PMA Certification Mark(seal) of the Pencil Makers Assoc. Inc. are not within the scope of the OSHA Hazard Communication Standard. Pencils and graphite products are articles, not chemicals, 29 C.F.R. part 1910 1200 (B)(5)

Pencil products bearing the PMA Certification Mark(seal) are certified in a program of toxicologic evaluation by a medical expert subject to review by the programs Toxicological review Bd. to contain no materials in sufficient quantities to offer an acute or chronic health hazard to humans.

No acute or chronic health labeling is required under provision of federal law, the federal hazardous substance act, or under ASTM Standard D 4236.

Section III -- Physical/Chemical Characteristics

Boiling Point	N/A	N/A	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg)	N/A	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	N/A			

Appearance and Odor
Solid Stick form----Cedar fragrance Dk. Grey--Black

Section IV -- Fire and Explosion Hazard Data

Flash Point (Method Used)	365° F	Flammable Limits	LEL N/A	UEL N/A
---------------------------	--------	------------------	---------	---------

Extinguishing Media
Foam, Carbon dioxide, dry chemical

Special Fire Fighting Procedures
A self contained breathing device should be used when there is potential exposure to combustion products burning in bulk.

Additional Fire and Explosion Hazards
Pencil products stored in bulk are subject to ignition by fire and may, in case of fire, release toxic and other irritating gases.

Section V — Reactivity Data

Stability	Unstable	N/A	Conditions to Avoid
	Stable	N/A	

Incompatibility (Materials to Avoid) N/A

Hazardous Decomposition or Byproducts N/A

Hazardous Polymerization	May Occur	N/A	Conditions to Avoid
	Will Not Occur	N/A	

Section VI — Health Hazard Data

Route(s) of Entry: N/A Inhalation? N/A Skin? N/A Ingestion? N/A

Health Hazards (Acute and Chronic) N/A

Carcinogenicity: N/A NTP? N/A IARC Monographs? N/A OSHA Regulated? N/A

Signs and Symptoms of Exposure N/A

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures N/A

Section VII — Precautions for Safe Handling and Use N/A

Steps to Be Taken in Case Material is Released or Spilled N/A

Waste Disposal Method N/A

Precautions to Be Taken in Handling and Storing N/A

Other Precautions N/A

Section VIII — Control Measures N/A

Respiratory Protection (Specify Type) N/A

Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A

Protective Gloves N/A Eye Protection N/A

Other Protective Clothing or Equipment N/A

Work/Hygiene Practices N/A